**KGB020-PP-AS** **Linear Ball Bearing and Housing Unit**

Linear ball bearing and housing unit; open design, sealed, greased, with relubrication facility; corrosion-resistant design possible

**Informacje techniczne****Twoja aktualna wersja produktu**

|      |    |
|------|----|
| Seal | PP |
|------|----|

|                       |    |
|-----------------------|----|
| Relubrication feature | AS |
|-----------------------|----|

**Technical data**

|   |           |
|---|-----------|
| 5 | Ball rows |
|---|-----------|

|    |         |      |
|----|---------|------|
| ≈m | 0,25 kg | Masa |
|----|---------|------|

**Main Dimensions & Performance Data**

|   |       |               |
|---|-------|---------------|
| H | 45 mm | Center height |
|---|-------|---------------|



|   |       |        |
|---|-------|--------|
| L | 45 mm | Length |
|---|-------|--------|

|       |     |           |
|-------|-----|-----------|
| Tol L | h12 | Tolerance |
|-------|-----|-----------|

|   |       |       |
|---|-------|-------|
| B | 70 mm | Width |
|---|-------|-------|

|   |         |                    |
|---|---------|--------------------|
| C | 1.600 N | Load capacity dyn. |
|---|---------|--------------------|

|                |         |                                    |
|----------------|---------|------------------------------------|
| C <sub>0</sub> | 1.280 N | Load capacity stat. C <sub>0</sub> |
|----------------|---------|------------------------------------|





Mounting dimensions

|         |            |                    |
|---------|------------|--------------------|
| J B     | 58 mm      |                    |
| Tol J B | + 0,15 mm  | Upper tolerance    |
| Tol J B | - 0,15 mm  | Lower tolerance    |
| B 1     | 45 mm      |                    |
| A 5     | 35 mm      |                    |
| Tol A 5 | + 0,02 mm  | Upper tolerance    |
| Tol A 5 | - 0,02 mm  | Lower tolerance    |
| B 2     | 10 mm      |                    |
| L 4     | 20 mm      | Distance           |
| L 5     | 28 mm      | Distance           |
| J L 4   | 9,5 mm     | Distance           |
| H 2     | 25 mm      | Height shaft       |
| Tol H 2 | + 0,015 mm | Upper tolerance    |
| Tol H 2 | - 0,015 mm | Lower tolerance    |
| A 3     | 21 mm      |                    |
| H 6     | 8 mm       |                    |
| N 1     | 6,6 mm     |                    |
| N 3     | 11 mm      |                    |
| K 5     | M6         |                    |
| K 8     | NIPA1      | Lubrication nipple |
| α       | 60 °       | Angle              |