


KGB030-PP-AS

Linear Ball Bearing and Housing Unit

Linear ball bearing and housing unit; open design, sealed, greased, with relubrication facility; corrosion-resistant design possible

Informacje techniczne



Twoja aktualna wersja produktu

Seal	PP
Relubrication feature	AS

Technical data

	5	Ball rows
≈m	0,78 kg	Masa

Main Dimensions & Performance Data

H	63,5 mm	Center height
L	68 mm	Length
Tol L	h12	Tolerance
B	88 mm	Width
C	3.700 N	Load capacity dyn.
C ₀	3.000 N	Load capacity stat. C ₀



Mounting dimensions

J B	76 mm	
Tol J B	+ 0,2 mm	Upper tolerance
Tol J B	- 0,2 mm	Lower tolerance
B 1	63 mm	
A 5	44 mm	
Tol A 5	+ 0,02 mm	Upper tolerance
Tol A 5	- 0,02 mm	Lower tolerance
B 2	13,6 mm	
L 4	32 mm	Distance
L 5	48 mm	Distance
J L 4	19 mm	Distance
H 2	35 mm	Height shaft
Tol H 2	+ 0,015 mm	Upper tolerance
Tol H 2	- 0,015 mm	Lower tolerance
A 3	25 mm	
H 6	10 mm	
N 1	6,6 mm	
N 3	11 mm	
K 5	M6	
K 8	NIPA2	Lubrication nipple
α	54 °	Angle