**KGB040-PP-AS** **Linear Ball Bearing and Housing Unit**

Linear ball bearing and housing unit; open design, sealed, greased, with relubrication facility; corrosion-resistant design possible

Informacje techniczne**Twoja aktualna wersja produktu**

Seal PP

Relubrication feature AS

Technical data

5 Ball rows

≈m 1,28 kg Masa

Main Dimensions & Performance Data

H 79,5 mm Center height



L 80 mm Length

Tol L h12 Tolerance

B 108 mm Width

C 6.100 N Load capacity dyn.

C₀ 4.600 N Load capacity stat. C₀





Mounting dimensions

J B	94 mm	
Tol J B	+ 0,2 mm	Upper tolerance
Tol J B	- 0,2 mm	Lower tolerance
B 1	77 mm	
A 5	54 mm	
Tol A 5	+ 0,02 mm	Upper tolerance
Tol A 5	- 0,02 mm	Lower tolerance
B 2	18,2 mm	
L 4	40 mm	Distance
L 5	56 mm	Distance
J L 4	23 mm	Distance
H 2	45 mm	Height shaft
Tol H 2	+ 0,015 mm	Upper tolerance
Tol H 2	- 0,015 mm	Lower tolerance
A 3	30 mm	
H 6	12 mm	
N 1	9 mm	
N 3	15 mm	
K 5	M8	
K 8	NIPA2	Lubrication nipple
α	54 °	Angle