




KGBS40-PP-AS

Linear Ball Bearing and Housing Unit

Linear ball bearing and housing unit;
adjustable, sealed, greased, with relubrication
facility; corrosion-resistant design possible

Informacje techniczne



Twoja aktualna wersja produktu

Size	40
Seal	PP
Relubrication feature	AS

Technical data

	6	Ball rows
≈m	1,43 kg	Masa

Main Dimensions & Performance Data

F _W	40 mm	Diameter of ball complement
H	83,5 mm	Height
L	80 mm	Length
Tol L	h12	Tolerance
B	108 mm	Width
C	6.000 N	Dynamic load rating
C ₀	4.400 N	Load capacity stat. C0



Mounting dimensions

J B	94 mm	
Tol J B	+ 0,2 mm	Upper tolerance
Tol J B	- 0,2 mm	Lower tolerance
B 1	77 mm	
A 5	54 mm	
Tol A 5	+ 0,02 mm	Upper tolerance
Tol A 5	- 0,02 mm	Lower tolerance
L 4	40 mm	Distance
L 5	56 mm	Distance
J L 4	28 mm	Distance
H 2	45 mm	Height shaft
Tol H 2	+ 0,015 mm	Upper tolerance
Tol H 2	- 0,015 mm	Lower tolerance
A 3	30 mm	
H 6	12 mm	
N 1	9 mm	
N 3	15 mm	
K 5	M8	
K 8	NIPA2	Lubrication nipple
W	4 mm	Width across flats