



IMAGE
COMING SOON





KGHK30-B-PP-AS

Linear Ball Bearing and Housing Unit

Linear ball bearing and housing unit; sealed, greased, with relubrication facility; corrosion-resistant design possible

Informacje techniczne




Twoja aktualna wersja produktu

Size	30
Version	B
Seal	PP
Relubrication feature	AS

Main Dimensions & Performance Data

F _W	30 mm	Diameter of ball complement
H	60 mm	Height
L	50,2 mm	Length
B	67 mm	Width
C	3.300 N	Dynamic load rating
C ₀	2.700 N	Basic static load capacity
≈m	0,419 kg	Masa



Mounting dimensions

J B	53 mm	
Tol J B	+ 0,15 mm	Upper tolerance
Tol J B	- 0,15 mm	Lower tolerance
B 1	49,6 mm	
A 5	33,5 mm	
H 2	30 mm	Center height
Tol H 2	+ 0,01 mm	Upper tolerance
Tol H 2	- 0,014 mm	Lower tolerance
H 4	42,7 mm	Mounting Dimension
H 5	8 mm	
T 5	18 mm	
H 6	29 mm	Mounting Dimension
A 3	18 mm	
G 2	M8	
N 1	6,6 mm	
N 3	15 mm	
K 5	M6	
K 8	NIPA2	Lubrication nipple