



IMAGE
COMING SOON






KGSNG25-PP-AS

Linear Ball Bearing and Housing Unit

Linear ball bearing and housing unit; with self-aligning linear ball bearing, sealed, greased, with relubrication facility

Informacje techniczne



Twoja aktualna wersja produktu

Size	25
Seal	PP
Relubrication feature	AS

Technical data

	8	Ball rows
≈m	0,63 kg	Masa

Main Dimensions & Performance Data

F w	25 mm	Diameter of ball complement
H	60 mm	Height
B	78 mm	Width
L	58 mm	Length
C max	3.950 N	Load capacity dyn.
C 0 max	4.300 N	Load capacity stat.



Mounting dimensions

J _B	60 mm	
Tol J _B	- 0,15 mm	Upper tolerance
Tol J _B	+ 0,15 mm	Lower tolerance
B ₁	59,4 mm	
A ₅	39 mm	
Tol A ₅	+ 0,01 mm	Upper tolerance
Tol A ₅	- 0,01 mm	Lower tolerance
J _L	40 mm	Distance
Tol J _L	+ 0,15 mm	Upper tolerance
Tol J _L	- 0,15 mm	Lower tolerance
H ₂	30 mm	Center height
Tol H ₂	+ 0,008 mm	Upper tolerance
Tol H ₂	- 0,016 mm	Lower tolerance
H ₄	41,5 mm	
H ₅	8,3 mm	
T ₅	22 mm	
H ₆	29 mm	
G ₂	M10	
N ₁	8,4 mm	
N ₄	6 mm	
N ₃	15 mm	
K ₅	M8	
K ₈	NIP5MZ	Lubrication nipple