



IMAGE  
COMING SOON






### KGSNG30-PP-AS

#### Linear Ball Bearing and Housing Unit

Linear ball bearing and housing unit; with self-aligning linear ball bearing, sealed, greased, with relubrication facility

#### Informacje techniczne



#### Twoja aktualna wersja produktu

|                       |    |
|-----------------------|----|
| Size                  | 30 |
| Seal                  | PP |
| Relubrication feature | AS |

#### Technical data

|    |         |           |
|----|---------|-----------|
|    | 8       | Ball rows |
| ≈m | 0,88 kg | Masa      |

#### Main Dimensions & Performance Data

|                    |         |                             |
|--------------------|---------|-----------------------------|
| F <sub>w</sub>     | 30 mm   | Diameter of ball complement |
| H                  | 70 mm   | Height                      |
| B                  | 87 mm   | Width                       |
| L                  | 68 mm   | Length                      |
| C <sub>max</sub>   | 5.900 N | Load capacity dyn.          |
| C <sub>0 max</sub> | 6.000 N | Load capacity stat.         |



Mounting dimensions

|                    |            |                    |
|--------------------|------------|--------------------|
| J <sub>B</sub>     | 68 mm      |                    |
| Tol J <sub>B</sub> | - 0,15 mm  | Upper tolerance    |
| Tol J <sub>B</sub> | + 0,15 mm  | Lower tolerance    |
| B <sub>1</sub>     | 63 mm      |                    |
| A <sub>5</sub>     | 43,5 mm    |                    |
| Tol A <sub>5</sub> | + 0,01 mm  | Upper tolerance    |
| Tol A <sub>5</sub> | - 0,01 mm  | Lower tolerance    |
| J <sub>L</sub>     | 45 mm      | Distance           |
| Tol J <sub>L</sub> | + 0,15 mm  | Upper tolerance    |
| Tol J <sub>L</sub> | - 0,15 mm  | Lower tolerance    |
| H <sub>2</sub>     | 35 mm      | Center height      |
| Tol H <sub>2</sub> | + 0,008 mm | Upper tolerance    |
| Tol H <sub>2</sub> | - 0,016 mm | Lower tolerance    |
| H <sub>4</sub>     | 46,2 mm    |                    |
| H <sub>5</sub>     | 9,3 mm     |                    |
| T <sub>5</sub>     | 22 mm      |                    |
| H <sub>6</sub>     | 34 mm      |                    |
| G <sub>2</sub>     | M10        |                    |
| N <sub>1</sub>     | 8,4 mm     |                    |
| N <sub>4</sub>     | 6 mm       |                    |
| N <sub>3</sub>     | 15 mm      |                    |
| K <sub>5</sub>     | M8         |                    |
| K <sub>8</sub>     | NIP5MZ     | Lubrication nipple |