




IMAGE  
COMING SOON**KGSNG40-PP-AS**

## Linear Ball Bearing and Housing Unit

Linear ball bearing and housing unit; with self-aligning linear ball bearing, sealed, greased, with relubrication facility

## Informacje techniczne



## Twoja aktualna wersja produktu

|                       |    |
|-----------------------|----|
| Size                  | 40 |
| Seal                  | PP |
| Relubrication feature | AS |

## Technical data

|    |         |           |
|----|---------|-----------|
|    | 8       | Ball rows |
| ≈m | 1,65 kg | Masa      |

## Main Dimensions &amp; Performance Data

|                    |          |                             |
|--------------------|----------|-----------------------------|
| F <sub>W</sub>     | 40 mm    | Diameter of ball complement |
| H                  | 90 mm    | Height                      |
| B                  | 108 mm   | Width                       |
| L                  | 80 mm    | Length                      |
| C <sub>max</sub>   | 10.200 N | Load capacity dyn.          |
| C <sub>0 max</sub> | 9.600 N  | Load capacity stat.         |



Mounting dimensions

|                    |            |                    |
|--------------------|------------|--------------------|
| J <sub>B</sub>     | 86 mm      |                    |
| Tol J <sub>B</sub> | - 0,15 mm  | Upper tolerance    |
| Tol J <sub>B</sub> | + 0,15 mm  | Lower tolerance    |
| B <sub>1</sub>     | 76 mm      |                    |
| A <sub>5</sub>     | 54 mm      |                    |
| Tol A <sub>5</sub> | + 0,01 mm  | Upper tolerance    |
| Tol A <sub>5</sub> | - 0,01 mm  | Lower tolerance    |
| J <sub>L</sub>     | 58 mm      | Distance           |
| Tol J <sub>L</sub> | + 0,15 mm  | Upper tolerance    |
| Tol J <sub>L</sub> | - 0,15 mm  | Lower tolerance    |
| H <sub>2</sub>     | 45 mm      | Center height      |
| Tol H <sub>2</sub> | + 0,008 mm | Upper tolerance    |
| Tol H <sub>2</sub> | - 0,016 mm | Lower tolerance    |
| H <sub>4</sub>     | 57,6 mm    |                    |
| H <sub>5</sub>     | 11,7 mm    |                    |
| T <sub>5</sub>     | 26 mm      |                    |
| H <sub>6</sub>     | 44 mm      |                    |
| G <sub>2</sub>     | M12        |                    |
| N <sub>1</sub>     | 10,5 mm    |                    |
| N <sub>4</sub>     | 8 mm       |                    |
| N <sub>3</sub>     | 18 mm      |                    |
| K <sub>5</sub>     | M10        |                    |
| K <sub>8</sub>     | NIP5MZ     | Lubrication nipple |