




KGSNO40-PP-AS [↗](#)

Linear Ball Bearing and Housing Unit

Linear ball bearing and housing unit; Heavy duty range, With segment cutout, without slot, sealed, greased, with relubrication facility

Informacje techniczne



Twoja aktualna wersja produktu

Size	40
Seal	PP
Relubrication feature	AS

Technical data

	6	Ball rows
≈m	1,4 kg	Masa

Main Dimensions & Performance Data

F _W	40 mm	Diameter of ball complement
H	77 mm	Height
L	80 mm	Length
B	108 mm	Width
C _{max}	10.200 N	Load capacity dyn.
C _{0 max}	9.600 N	Load capacity stat.



Mounting dimensions

J B	86 mm	
Tol J B	+ 0,15 mm	Upper tolerance
Tol J B	- 0,15 mm	Lower tolerance
B 2	18,2 mm	
A 5	54 mm	
Tol A 5	+ 0,01 mm	Upper tolerance
Tol A 5	- 0,01 mm	Lower tolerance
J L	58 mm	Distance
Tol J L	+ 0,15 mm	Upper tolerance
Tol J L	- 0,15 mm	Lower tolerance
H 2	45 mm	Center height
Tol H 2	+ 0,008 mm	Upper tolerance
Tol H 2	- 0,016 mm	Lower tolerance
H 5	12,4 mm	
T 5	26 mm	
H 6	44 mm	
G 2	M12	
N 1	10,5 mm	
N 4	3.15x6.7	
N 3	18 mm	
K 5	M10	
K 8	NIP5MZ	Lubrication nipple
α	56 °	Angle