



FAG

KLM67048-LM67010

Tapered roller bearing

Tapered roller bearings K-Series, in inch sizes, separable

Informacje techniczne



Twoja aktualna wersja produktu

Tolerance class	ABMA4	Class 4 (ANSI/ABMA 19.2:2013)
Heat treatment	Standard	
Cage	Standard	Sheet steel cage, window cage, roller-guided
Quality level	Standard	
Number of rows	1	Single-row design

Main Dimensions & Performance Data

d	31,75 mm	Bore diameter
D	59,131 mm	Outside diameter
B	16,764 mm	Width, inner ring
C	11,811 mm	Width, outer ring
T	15,875 mm	Width, total
C _r	34.000 N	Basic dynamic load rating, radial
C _{0r}	40.000 N	Basic static load rating, radial
C _{ur}	4.500 N	Fatigue load limit, radial
n _G	12.800 1/min	Limiting speed
n _{gr}	7.500 1/min	Thermal speed rating
≈m	0,18 kg	Masa



Mounting dimensions

$d_{a \max}$	36 mm	Maximum diameter of shaft shoulder
$d_{b \min}$	42,5 mm	Minimum diameter of shaft shoulder
$D_{a \min}$	52 mm	Minimum diameter of housing shoulder
$D_{b \min}$	56 mm	Minimum diameter of housing shoulder
$C_{a \min}$	3,5 mm	Minimum axial space
$C_{b \min}$	4 mm	Minimum axial space
$r_{a \max}$	3,6 mm	Maximum fillet radius of shaft
$r_{b \max}$	1,3 mm	Maximum fillet radius of housing

Dimensions

$r_{1, 2 \min}$	3,6 mm	Minimum chamfer dimension of inner ring back face
$r_{3, 4 \min}$	1,3 mm	Minimum chamfer dimension of outer ring back face
a	13 mm	Distance between the apexes of the pressure cones
d_1	45,8 mm	Guidance rib diameter of inner ring

Temperature range

$T_{\min}$	-30 °C	Operating temperature min.
$T_{\max}$	120 °C	Operating temperature max.

Calculation factors

e	0,41	Limiting value of F_a/F_r for the applicability of diff. Values of factors X and Y
Y	1,46	Dynamic axial load factor
Y_0	0,8	Static axial load factor



Właściwości



Obciążenie promieniowe



Obciążenie osiowe jednokierunkowe



Smarowanie smarem



Smarowanie olejem



Bez uszczelnienia