


KR90-PP-A

Stud type track roller

Stud type track rollers KR..-PP-A, single row needle roller bearings with particularly thick-walled outer ring, needle roller and cage assembly and a solid roller stud with fixing thread and a mounting aid, axial guidance of outer ring is provided by the plastic axial plain washers, contact flange and contact washer, three-stage sealing by plastic axial plain washer on both sides, without eccentric collar

Informacje techniczne



Twoja aktualna wersja produktu

Sealing	PP	Three-stage sealing by plastic axial plain washer on both sides
Outer ring profile	IOP	Optimized INA-profile
Grease nipples	2x	Drive-fit lubrication nipple unmounted 2x
Relubrication feature	KSP	Via head, stud and fit
Assembling aid head	I6	Hexagon socket
Assembling aid stud	I6	Hexagon socket

Main Dimensions & Performance Data

D	90 mm	Outside diameter
d 1	30 mm	Fit diameter of roller stud / stud
B	100 mm	Width of the roller stud
C r w	40.500 N	Basic dynamic load rating, radial
C 0r w	84.000 N	Basic static load rating, radial
C ur w	11.900 N	Fatigue load limit, radial
n D G	1.300 1/min	Speed on permanent grease lubrication
≈m	1,942 kg	Masa



Dimensions

B 1	37 mm	Maximum width of thrust washer
B 2	63 mm	Bolt/stud length effectively
B 3	15 mm	Distance to lubrication hole
C	35 mm	Width, outer ring
C 1	1 mm	Protrusion outer ring to thrust washer
r min	1,1 mm	Minimum chamfer dimension
d 2	53 mm	Stop diameter of thrust washer
d 3	4 mm	Diameter lubrication hole
G	M30X1,5	Thread
l G	32 mm	Thread length
W	14 mm	Width of flats

Additional information

	NIPA3X9,5	Drive-fit lubrication nipple
M A	450 Nm	Tightening torque nut

Właściwości

	Obciążenie promieniowe
	Smarowanie dożywotnie, bezobsługowe
	Smarowanie smarem
	Uszczelnienie dwustronne