

KRV19-PP

Stud type track roller

Stud type track rollers KRV..-PP-A, single row needle roller bearings with particularly thick-walled outer ring, full complement needle roller set and with a solid roller stud with fixing thread and a mounting aid, axial guidance of outer ring is provided by the plastic axial plain washers, contact flange and contact washer, three-stage sealing by plastic axial plain washer on both sides, without eccentric collar

Informacje techniczne



Twoja aktualna wersja produktu

Sealing	PP	Three-stage sealing by plastic axial plain washer on both sides
Outer ring profile	IOP	Optimized INA-profile
Grease nipples	1x	Drive-fit lubrication nipple unmounted 1x
Relubrication feature	K	Via head
Assembling aid head	SL	Mounting slot

Main Dimensions & Performance Data

D	19 mm	Outside diameter
d_1	8 mm	Fit diameter of roller stud / stud
B	32 mm	Width
$C_{r\,w}$	5.400 N	Basic dynamic load rating, radial
$C_{0r\,w}$	8.100 N	Basic static load rating, radial
$C_{ur\,w}$	1.190 N	Fatigue load limit, radial
$n_{D\,G}$	3.100 1/min	Speed on permanent grease lubrication
≈m	28,754 g	Masa

Karta katalogowa jest jedynie przeglądem wymiarów i podstawowych nośności wybranego produktu. Zawsze należy stosować się do wszystkich dalszych informacji i instrukcji dotyczących tego produktu. Na naszej stronie internetowej znajduje się formularz kontaktowy umożliwiający wysłanie zapytania o dalsze informacje

Dimensions

B_1	12,2 mm	Witdh of thrust washer
B_2	20 mm	Bolt/stud length effectively
C	11 mm	Width, outer ring
C_1	0,6 mm	Protrusion outer ring to thrust washer
r_{min}	0,15 mm	Minimum chamfer dimension
d_2	15 mm	Stop diameter of thrust washer
G	M8	Thread
l_G	10 mm	Thread length

Additional information

	NIPA1	Drive-fit lubrication nipple
	1,5 mm	Protrusion lubrication nipple
M_A	8 Nm	Tightening torque nut

Właściwości

- Obciążenie promieniowe
- Smarowanie dożywotnie, bezobsługowe
- Smarowanie smarem
- Uszczelnienie dwustronne

Karta katalogowa jest jedynie przeglądem wymiarów i podstawowych nośności wybranego produktu. Zawsze należy stosować się do wszystkich dalszych informacji i instrukcji dotyczących tego produktu. Na naszej stronie internetowej znajduje się formularz kontaktowy umożliwiający wysłanie zapytania o dalsze informacje