




KWEM07-E-WL-V0-G2

Miniature Carriage, Standard for Miniature-Guideway, Standard

Miniature-Carriage, Wide-Long design; for
Miniature guideway, Wide design

Informacje techniczne



Twoja aktualna wersja produktu

Size	07	
Version	E	
Carriage design	WL	Wide, long design
Preload class	V0	Slight clearance
Accuracy class	G2	

Main Dimensions & Performance Data

H	9 mm	Height system
B	25 mm	Width carriage
L	41,5 mm	Length of carriage
C	1.660 N	Dynamic load rating
C ₀	3.450 N	Basic static load capacity
M _{0x}	23 Nm	Static moment rating about X axis
M _{0y}	15,8 Nm	Static moment rating about Y axis
M _{0z}	15,8 Nm	Static moment rating about Z axis
≈m	34 g	Masa



Mounting dimensions

b	14 mm	Width rail
A 1	55 mm	Distance from locating edge on carriage to locating edge on guideway
A 2	3 mm	Distance from locating edge to hole
H 1	2 mm	Free space, system dimension
J B	19 mm	Hole spacing
J L	19 mm	Hole Spacing
T 5	3 mm	Thread depth
A 3	1,7 mm	Position lubrication connector
G2	M3	Thread size
G2 M A	1,1 Nm	Maximum tightening torque

Additional information

VMKB_065	KWEM	Material name
----------	------	---------------