


KWLT25-US-V0-G3

Recirculating ball bearing carriage

Short & slim carriage, standard end plate, for four-row linear recirculating ball bearing and guideway assembly

Informacje techniczne



Twoja aktualna wersja produktu

Size	25	
Carriage design	US	Short, high design
Preload class	V0	Slight clearance
Accuracy class	G3	

Main Dimensions & Performance Data

H	36 mm	Height system
B	48 mm	Width carriage
L	63,6 mm	Overall length carriage
C	14.900 N	Dynamic load rating
C ₀	24.300 N	Basic static load capacity
M _{0x}	320 Nm	Static moment rating about X-axis
M _{0y}	163 Nm	Static moment rating about Y-axis
M _{0z}	163 Nm	Static moment rating about Z-axis
M _{0x}	183 Nm	Dynamic moment rating about X-axis
M _{0y}	153 Nm	Dynamic moment rating about y-axis
M _{0z}	153 Nm	Dynamic moment rating about Z-axis
≈m	320 g	Masa



Mounting dimensions

A 1	12,5 mm	Distance from locating edge on carriage to locating edge on guideway
A 2	6,5 mm	Distance from locating edge to hole
L 1	38,8 mm	Carrier length
H 1	7 mm	Free space, system dimension
J B	35 mm	Hole spacing
A 3	6,5 mm	Position lubrication connector
T 5	6,5 mm	Thread depth
G 2	M6	Thread size, DIN ISO 4762-12.9
G2 M A	16,5 Nm	Maximum tightening torque

Additional information

VMKB_065	KWLT	Material name
----------	------	---------------