



KWLT35-S-V1-G4

Recirculating ball bearing carriage

Slim carriage, standard end plate, for four-row linear recirculating ball bearing and guideway assembly

Informacje techniczne



Twoja aktualna wersja produktu

Size	35	
Carriage design	S	Narrow design
Preload class	V1	Slight preload (standard)
Accuracy class	G4	

Main Dimensions & Performance Data

H	48 mm	Height system
B	70 mm	Width carriage
L	114 mm	Overall length carriage
C	36.500 N	Dynamic load rating
C ₀	65.000 N	Basic static load capacity
M _{0x}	1.270 Nm	Static moment rating about X-axis
M _{0y}	800 Nm	Static moment rating about Y-axis
M _{0z}	800 Nm	Static moment rating about Z-axis
M _{0x}	664 Nm	Dynamic moment rating about X-axis
M _{0y}	746 Nm	Dynamic moment rating about y-axis
M _{0z}	746 Nm	Dynamic moment rating about Z-axis
≈m	1,15 kg	Masa



Mounting dimensions

A 1	18 mm	Distance from locating edge on carriage to locating edge on guideway
A 2	10 mm	Distance from locating edge to hole
L 1	77 mm	Carrier length
H 1	9,5 mm	Free space, system dimension
J B	50 mm	Hole spacing
J L	50 mm	Hole Spacing
A 3	8 mm	Position lubrication connector
T 5	10 mm	Thread depth
G 2	M8	Thread size, DIN ISO 4762-12.9
G2 M A	40 Nm	Maximum tightening torque

Additional information

VMKB_065	KWLT	Material name
----------	------	---------------