

**LFR5206-25-2RS-RB**

Yoke type track roller

Yoke type track roller

## Informacje techniczne



## Twoja aktualna wersja produktu

|          |      |                            |
|----------|------|----------------------------|
| Size     | 5206 |                            |
| Seal     | 2RS  | Double-sided sliding seal  |
| Material | RB   | Corrosion-resistant design |

## Main Dimensions &amp; Performance Data

|                  |          |                   |
|------------------|----------|-------------------|
| d                | 25 mm    |                   |
| D <sub>max</sub> | 72 mm    |                   |
| B                | 25,8 mm  | Width, inner ring |
| ≈m               | 0,381 kg | Masa              |

## Mounting dimensions

|                  |          |                     |
|------------------|----------|---------------------|
| A <sub>T</sub>   | 43,5 mm  |                     |
| C                | 23,8 mm  |                     |
| D <sub>a</sub>   | 65,35 mm | Diameter of rolling |
| d <sub>s</sub>   | 25 mm    |                     |
| r <sub>min</sub> | 1 mm     |                     |

## Main dimensions

|                     |          |                                                        |
|---------------------|----------|--------------------------------------------------------|
| C <sub>r w</sub>    | 22.700 N | Effective dynamic load rating as track roller (radial) |
| C <sub>0r w</sub>   | 16.100 N | Effective static load rating as track roller (radial)  |
| C <sub>ur w</sub>   | 850 N    | Limit of fatigue load                                  |
| F <sub>r per</sub>  | 18.800 N | Permissible dynamic limit load                         |
| F <sub>0r per</sub> | 32.000 N | Permissible static limit load                          |



Additional information

LFE/LFZ      siehe Katalog: LF1      Possible roller-pin combination