


**LR50/8-2RSR**

Yoke type track roller

Yoke type track rollers LR50..-2RS/2RSR, double row self-retaining angular contact ball bearings with particularly thick-walled outer ring, ball and cage assembly and an inner ring, axial guidance of outer ring is provided by the balls, lip seal on both sides, with axial sealing action/with radial sealing action

Informacje techniczne



Twoja aktualna wersja produktu

|                       |      |                                                    |
|-----------------------|------|----------------------------------------------------|
| Sealing               | 2RSR | Lip seal on both sides, with radial sealing action |
| Outer ring profile    | R500 | R500                                               |
| Relubrication feature | IR   | Via inner ring lubrication hole                    |

Main Dimensions & Performance Data

|                    |              |                                       |
|--------------------|--------------|---------------------------------------|
| D                  | 24 mm        | Outside diameter                      |
| d                  | 8 mm         | Bore diameter                         |
| C                  | 11 mm        | Height                                |
| C <sub>r w</sub>   | 4.300 N      | Effective dynamic load rating, radial |
| C <sub>0 r w</sub> | 2.460 N      | Effective static load rating, radial  |
| C <sub>u r w</sub> | 122 N        | Effective fatigue limit load, radial  |
| n <sub>D G</sub>   | 10.000 1/min | Speed on permanent grease lubrication |
| F <sub>r per</sub> | 2.460 N      | Permissible dynamic load, radial      |
| m                  | 0,03 kg      | Masa                                  |

Dimensions

|                  |         |                                      |
|------------------|---------|--------------------------------------|
| d <sub>2</sub>   | 10,5 mm | Diameter of thrust washer            |
| r <sub>min</sub> | 0,3 mm  | Minimum chamfer dimension            |
| R                | 500 mm  | Radius of outer ring outside profile |



### Właściwości



Obciążenie promieniowe



Obciążenie osiowe jednokierunkowe



Obciążenie osiowe dwukierunkowe



Smarowanie dożywotnie, bezobsługowe



Smarowanie smarem



Uszczelnienie dwustronne