




**LUHR40**

Linear ball bearing and housing unit

Linear bearing unit, compact range, shielded

Informacje techniczne



Twoja aktualna wersja produktu

|                 |    |
|-----------------|----|
| Size            | 40 |
| Number of seals | 0  |

Technical data

|           |                      |                      |
|-----------|----------------------|----------------------|
| $v_{max}$ | 5 m/s                | Maximum Speed        |
| $a_{max}$ | 100 m/s <sup>2</sup> | Maximum Acceleration |
| $m$       | 0,74 kg              | Masa                 |

Main Dimensions & Performance Data

|                    |         |                     |
|--------------------|---------|---------------------|
| N                  | 8,4 mm  | Bore diameter       |
| H <sub>2</sub>     | 38 mm   | Height              |
| D <sub>a</sub>     | 52 mm   | Bore diameter       |
| F <sub>w</sub>     | 40 mm   | Bore diameter       |
| C <sub>max</sub>   | 5.400 N | Load capacity dyn.  |
| C <sub>min</sub>   | 5.500 N | Load capacity dyn.  |
| C <sub>0 min</sub> | 4.500 N | Load capacity stat. |
| C <sub>0 max</sub> | 5.000 N | Load capacity stat. |

Dimensions

|                |       |                    |
|----------------|-------|--------------------|
| H <sub>1</sub> | 76 mm | Height of Carriage |
| H <sub>3</sub> | 22 mm | Height             |



Mounting dimensions

|     |       |               |
|-----|-------|---------------|
| H   | 39 mm | Center height |
| J   | 69 mm |               |
| N 1 | M10   | Thread        |
| L   | 87 mm |               |
| A   | 60 mm | Length        |