




FAG

N212-E-XL-M1>A

Cylindrical roller bearing

Cylindrical roller bearing N2...M1, with cage, single row, non-locating bearing, 0 ribs on outer ring, 2 rib on inner ring, type N2

Informacje techniczne



Twoja aktualna wersja produktu

Cage	M1	Two Piece Brass Cage Roller Guided
Tolerance class	PN	Normal (ISO 492:2023)
Change mark	E	Increased Capacity Design
Radial internal clearance	CN (Group N)	Normal internal clearance
Number of rows	1	Single-row design

Main Dimensions & Performance Data

d	60 mm	Bore diameter
D	110 mm	Outside diameter
B	22 mm	Width
C _r	112.000 N	Basic dynamic load rating, radial
C _{0r}	103.000 N	Basic static load rating, radial
C _{ur}	17.800 N	Fatigue load limit, radial
≈m	0,91 kg	Masa

Mounting dimensions

d _a	69 mm	Diameter shaft shoulder
D _a	101 mm	Diameter of housing shoulder
r _{a1 max}	1,5 mm	Maximum recess radius

Dimensions

r _{1 min}	1,5 mm	Minimum chamfer dimension
E	100 mm	Raceway diameter outer ring



Temperature range

T_{min}	-30 °C	Operating temperature min.
T_{max}	150 °C	Operating temperature max.

Właściwości

-  Obciążenie promieniowe
-  Smarowanie smarem
-  Smarowanie olejem
-  Bez uszczelnienia