




FAG

N316-E-XL-M1-C3

Cylindrical roller bearing

Cylindrical roller bearing N3...E-M1, with cage, single row, non-locating bearing, 0 ribs on outer ring, 2 rib on inner ring, type N3

Informacje techniczne



Twoja aktualna wersja produktu

Cage	M1	Two Piece Brass Cage Roller Guided
Tolerance class	PN	Normal (ISO 492:2023)
Change mark	E	Increased Capacity Design
Radial internal clearance	C3 (Group 3)	Internal clearance larger than CN
Number of rows	1	Single-row design

Main Dimensions & Performance Data

d	80 mm	Bore diameter
D	170 mm	Outside diameter
B	39 mm	Width
C _r	300.000 N	Basic dynamic load rating, radial
C _{0r}	275.000 N	Basic static load rating, radial
C _{ur}	49.500 N	Fatigue load limit, radial
≈m	4,372 kg	Masa

Mounting dimensions

D _a	158 mm	Diameter of housing shoulder
r _{a1 max}	2 mm	Maximum recess radius

Dimensions

r _{1 min}	2,1 mm	Minimum chamfer dimension
--------------------	--------	---------------------------



Temperature range

$T_{\min}$	-30 °C	Operating temperature min.
$T_{\max}$	150 °C	Operating temperature max.

Właściwości

-  Obciążenie promieniowe
-  Smarowanie smarem
-  Smarowanie olejem
-  Bez uszczelnienia