


NATR17

Yoke type track roller

Yoke type track rollers NATR..., single row needle roller bearings with particularly thick-walled outer ring, needle roller and cage assembly and an inner ring, axial guidance of outer ring is provided by the contact washers, gap seals on both sides

Informacje techniczne



Twoja aktualna wersja produktu

Sealing	SPSP	Gap seal on both sides
Outer ring profile	R500	R500
Relubrication feature	IR	Via inner ring

Main Dimensions & Performance Data

d	17 mm	Bore diameter
D	40 mm	Outside diameter
B	21 mm	Width of the bearing
C _{r w}	10.900 N	Basic dynamic load rating, radial
C _{0r w}	16.000 N	Basic static load rating, radial
C _{ur w}	2.130 N	Fatigue load limit, radial
n _{D G}	2.900 1/min	Speed on permanent grease lubrication
F _{0r per}	16.000 N	Permissible static load, radial
F _{r per}	16.000 N	Permissible dynamic load outer ring, radial
≈m	0,148 kg	Masa

Dimensions

C	20 mm	Width, outer ring
d ₂	31,5 mm	Outside diameter of thrust washer
r _{min}	1 mm	Minimum chamfer dimension
R	500 mm	Radius of outer ring outside profile



Właściwości



Obciążenie promieniowe



Smarowanie smarem



Smarowanie olejem



Bez uszczelnienia