


NATR5

Yoke type track roller

Yoke type track rollers NATR..., single row needle roller bearings with particularly thick-walled outer ring, needle roller and cage assembly and an inner ring, axial guidance of outer ring is provided by the contact washers, gap seals on both sides

Informacje techniczne



Twoja aktualna wersja produktu

|                       |      |                        |
|-----------------------|------|------------------------|
| Sealing               | SPSP | Gap seal on both sides |
| Outer ring profile    | R500 | R500                   |
| Relubrication feature | IR   | Via inner ring         |

Main Dimensions & Performance Data

|                     |              |                                             |
|---------------------|--------------|---------------------------------------------|
| d                   | 5 mm         | Bore diameter                               |
| D                   | 16 mm        | Outside diameter                            |
| B                   | 12 mm        | Width of the bearing                        |
| C <sub>r w</sub>    | 3.200 N      | Basic dynamic load rating, radial           |
| C <sub>0r w</sub>   | 3.450 N      | Basic static load rating, radial            |
| C <sub>ur w</sub>   | 465 N        | Fatigue load limit, radial                  |
| n <sub>D G</sub>    | 14.000 1/min | Speed on permanent grease lubrication       |
| F <sub>0r per</sub> | 3.450 N      | Permissible static load, radial             |
| F <sub>r per</sub>  | 3.450 N      | Permissible dynamic load outer ring, radial |
| ≈m                  | 15,1 g       | Masa                                        |

Dimensions

|                  |         |                                      |
|------------------|---------|--------------------------------------|
| C                | 11 mm   | Width, outer ring                    |
| d <sub>2</sub>   | 12,5 mm | Outside diameter of thrust washer    |
| r <sub>min</sub> | 0,15 mm | Minimum chamfer dimension            |
| R                | 500 mm  | Radius of outer ring outside profile |



### Właściwości

---



Obciążenie promieniowe



Smarowanie smarem



Smarowanie olejem



Bez uszczelnienia