
**NATV25** **Yoke type track roller**

Yoke type track rollers NATV..., single row needle roller bearings with particularly thick-walled outer ring, full complement needle roller set and an inner ring, axial guidance of outer ring is provided by the contact washers, gap seals on both sides

**Informacje techniczne****Twoja aktualna wersja produktu**

|                    |      |                        |
|--------------------|------|------------------------|
| Sealing            | SPSP | Gap seal on both sides |
| Outer ring profile | R500 | R500                   |

**Main Dimensions & Performance Data**

|                     |             |                                             |
|---------------------|-------------|---------------------------------------------|
| d                   | 25 mm       | Bore diameter                               |
| D                   | 52 mm       | Outside diameter                            |
| B                   | 25 mm       | Width of the bearing                        |
| C <sub>r w</sub>    | 20.100 N    | Basic dynamic load rating, radial           |
| C <sub>0r w</sub>   | 44.500 N    | Basic static load rating, radial            |
| C <sub>ur w</sub>   | 6.300 N     | Fatigue load limit, radial                  |
| n <sub>D G</sub>    | 1.000 1/min | Speed on permanent grease lubrication       |
| F <sub>0r per</sub> | 44.500 N    | Permissible static load, radial             |
| F <sub>r per</sub>  | 43.500 N    | Permissible dynamic load outer ring, radial |
| ≈m                  | 294,13 g    | Masa                                        |

**Dimensions**

|                  |         |                                      |
|------------------|---------|--------------------------------------|
| C                | 24 mm   | Width, outer ring                    |
| d <sub>2</sub>   | 41,5 mm | Outside diameter of thrust washer    |
| r <sub>min</sub> | 1 mm    | Minimum chamfer dimension            |
| R                | 500 mm  | Radius of outer ring outside profile |



### Właściwości

---

-  Obciążenie promieniowe
-  Smarowanie smarem
-  Smarowanie olejem
-  Bez uszczelnienia