



FAG


NJ2203-E-XL-M1A

Cylindrical roller bearing

Cylindrical roller bearing NJ..-E-XL-M1A, with cage, single row, semi-locating bearing, 2 ribs on outer ring, 1 rib on inner ring, type NJ

X-life

Informacje techniczne



Twoja aktualna wersja produktu

|                           |              |                                 |
|---------------------------|--------------|---------------------------------|
| Design                    | E            | Increased Capacity Design       |
| Cage                      | M1A          | Two Piece Brass Cage Lip guided |
| Radial internal clearance | CN (Group N) | Normal internal clearance       |
| Tolerance class           | PN           | Normal (ISO 492:2023)           |
| Number of rows            | 1            | Single-row design               |

Main Dimensions & Performance Data

|                 |              |                                   |
|-----------------|--------------|-----------------------------------|
| d               | 17 mm        | Bore diameter                     |
| D               | 40 mm        | Outside diameter                  |
| B               | 16 mm        | Width                             |
| C <sub>r</sub>  | 28.500 N     | Basic dynamic load rating, radial |
| C <sub>0r</sub> | 21.900 N     | Basic static load rating, radial  |
| C <sub>ur</sub> | 3.550 N      | Fatigue load limit, radial        |
| n <sub>G</sub>  | 34.000 1/min | Limiting speed                    |
| n <sub>gr</sub> | 13.200 1/min | Reference speed                   |
| m               | 106,4 g      | Masa                              |



Mounting dimensions

|                    |         |                                      |
|--------------------|---------|--------------------------------------|
| d <sub>a min</sub> | 21 mm   | Minimum diameter shaft shoulder      |
| d <sub>a max</sub> | 21,5 mm | Maximum diameter of shaft shoulder   |
| D <sub>a max</sub> | 36 mm   | Maximum diameter of housing shoulder |
| d <sub>c min</sub> | 26 mm   | Minimum shaft shoulder               |
| r <sub>a max</sub> | 0,6 mm  | Maximum recess radius                |

Dimensions

|                    |         |                                 |
|--------------------|---------|---------------------------------|
| r <sub>min</sub>   | 0,6 mm  | Minimum chamfer dimension       |
| r <sub>1 min</sub> | 0,3 mm  | Minimum chamfer dimension       |
| s                  | 1,7 mm  | Axial displacement              |
| E                  | 35,1 mm | Raceway diameter outer ring     |
| F                  | 22,1 mm | Raceway diameter inner ring     |
| D <sub>1 min</sub> | 32,5 mm | Minimum rib diameter outer ring |
| d <sub>1</sub>     | 24,7 mm | Maximum rib diameter inner ring |

Temperature range

|                  |        |                            |
|------------------|--------|----------------------------|
| T <sub>min</sub> | -30 °C | Operating temperature min. |
| T <sub>max</sub> | 150 °C | Operating temperature max. |

Additional information

|          |          |
|----------|----------|
| HJ2203-E | L-washer |
|----------|----------|

Właściwości

|  |                                   |
|--|-----------------------------------|
|  | Obciążenie promieniowe            |
|  | Obciążenie osiowe jednokierunkowe |
|  | Smarowanie smarem                 |
|  | Smarowanie olejem                 |
|  | Bez uszczelnienia                 |