



FAG


NJ2204-E-XL-M1A-C4

Cylindrical roller bearing

Cylindrical roller bearing NJ...E-XL-M1A, with cage, single row, semi-locating bearing, 2 ribs on outer ring, 1 rib on inner ring, type NJ

X-life

Informacje techniczne



Twoja aktualna wersja produktu

Design	E	Increased Capacity Design
Cage	M1A	Two Piece Brass Cage Lip guided
Radial internal clearance	C4 (Group 4)	Internal clearance larger than C3
Tolerance class	PN	Normal (ISO 492:2023)
Number of rows	1	Single-row design

Main Dimensions & Performance Data

d	20 mm	Bore diameter
D	47 mm	Outside diameter
B	18 mm	Width
C _r	38.500 N	Basic dynamic load rating, radial
C _{0r}	31.000 N	Basic static load rating, radial
C _{ur}	5.200 N	Fatigue load limit, radial
n _G	28.500 1/min	Limiting speed
n _{gr}	11.100 1/min	Reference speed
m	167,56 g	Masa



Mounting dimensions

d _{a min}	24 mm	Minimum diameter shaft shoulder
d _{a max}	26 mm	Maximum diameter of shaft shoulder
D _{a max}	41 mm	Maximum diameter of housing shoulder
d _{c min}	32 mm	Minimum shaft shoulder
r _{a max}	1 mm	Maximum recess radius

Dimensions

r _{min}	1 mm	Minimum chamfer dimension
r _{1 min}	0,6 mm	Minimum chamfer dimension
s	1,8 mm	Axial displacement
E	41,5 mm	Raceway diameter outer ring
F	26,5 mm	Raceway diameter inner ring
D _{1 min}	38,8 mm	Minimum rib diameter outer ring
d ₁	29,7 mm	Maximum rib diameter inner ring

Temperature range

T _{min}	-30 °C	Operating temperature min.
T _{max}	150 °C	Operating temperature max.

Additional information

HJ2204-E	L-washer
----------	----------

Właściwości

	Obciążenie promieniowe
	Obciążenie osiowe jednokierunkowe
	Smarowanie smarem
	Smarowanie olejem
	Bez uszczelnienia