



FAG

NJ2220-E-XL-M1

Cylindrical roller bearing

Cylindrical roller bearing NJ..-E-XL-M1, with cage, single row, semi-locating bearing, 2 ribs on outer ring, 1 rib on inner ring, type NJ

X-life

Informacje techniczne




Twoja aktualna wersja produktu

Design	E	Increased Capacity Design
Cage	M1	Two Piece Brass Cage Roller Guided
Radial internal clearance	CN (Group N)	Normal internal clearance
Tolerance class	PN	Normal (ISO 492:2023)
Number of rows	1	Single-row design

Main Dimensions & Performance Data

d	100 mm	Bore diameter
D	180 mm	Outside diameter
B	46 mm	Width
C _r	395.000 N	Basic dynamic load rating, radial
C _{0r}	445.000 N	Basic static load rating, radial
C _{ur}	77.000 N	Fatigue load limit, radial
n _G	6.800 1/min	Limiting speed
n _{gr}	2.900 1/min	Reference speed
≈m	5,3 kg	Masa



Mounting dimensions

$d_a \text{ min}$	112 mm	Minimum diameter shaft shoulder
$d_a \text{ max}$	117 mm	Maximum diameter of shaft shoulder
$D_a \text{ max}$	168 mm	Maximum diameter of housing shoulder
$d_c \text{ min}$	130 mm	Minimum shaft shoulder
$r_a \text{ max}$	2 mm	Maximum recess radius

Dimensions

r_{min}	2,1 mm	Minimum chamfer dimension
$r_1 \text{ min}$	2,1 mm	Minimum chamfer dimension
s	2,5 mm	Axial displacement
E	163 mm	Raceway diameter outer ring
F	119 mm	Raceway diameter inner ring
$D_1 \text{ min}$	156,9 mm	Minimum rib diameter outer ring
d_1	127,3 mm	Maximum rib diameter inner ring

Temperature range

T_{min}	-30 °C	Operating temperature min.
T_{max}	150 °C	Operating temperature max.

Additional information

HJ2220-E

L-washer

Właściwości



Obciążenie promieniowe



Obciążenie osiowe jednokierunkowe



Smarowanie smarem



Smarowanie olejem



Bez uszczelnienia