



FAG


NJ2328-E-XL-MCA

Cylindrical roller bearing

Cylindrical roller bearing NJ..-E-XL-MCA, with cage, single row, semi-locating bearing, 2 ribs on outer ring, 1 rib on inner ring, type NJ

X-life

Informacje techniczne



Twoja aktualna wersja produktu

Design	E	Increased Capacity Design
Number of rows	1	Single-row design

Main Dimensions & Performance Data

d	140 mm	Bore diameter
D	300 mm	Outside diameter
B	102 mm	Width
C _r	1.210.000 N	Basic dynamic load rating, radial
C _{0r}	1.390.000 N	Basic static load rating, radial
C _{ur}	221.000 N	Fatigue load limit, radial
n _G	3.950 1/min	Limiting speed
n _{gr}	1.620 1/min	Reference speed
≈m	35,9 kg	Masa

Mounting dimensions

d _{a min}	157 mm	Minimum diameter shaft shoulder
d _{a max}	176 mm	Maximum diameter of shaft shoulder
D _{a max}	283 mm	Maximum diameter of housing shoulder
d _{c min}	198 mm	Minimum shaft shoulder
r _{a max}	3 mm	Maximum recess radius



Dimensions

r _{min}	4 mm	Minimum chamfer dimension
r _{1 min}	4 mm	Minimum chamfer dimension
s	9,2 mm	Axial displacement
E	264 mm	Raceway diameter outer ring
F	180 mm	Raceway diameter inner ring
D _{1 min}	251,7 mm	Minimum rib diameter outer ring
d ₁	195,4 mm	Maximum rib diameter inner ring

Temperature range

T _{min}	-30 °C	Operating temperature min.
T _{max}	150 °C	Operating temperature max.

Additional information

HJ2328-E	L-washer
----------	----------

Właściwości

- 

Obciążenie promieniowe
- 

Obciążenie osiowe jednokierunkowe
- 

Smarowanie smarem
- 

Smarowanie olejem
- 

Bez uszczelnienia