




FAG

NJ2332-E-XL-MPAX-QP51-ILR-C4

Cylindrical roller bearing

Cylindrical roller bearing NJ...E...MPAX-ILR, with cage, single row, semi-locating bearing, 2 ribs on outer ring, 1 rib on inner ring, type NJ

Informacje techniczne



Twoja aktualna wersja produktu

Design	E	Increased Capacity Design
Cage	MPAX	One Piece Brass Cage Lip Guided
Radial internal clearance	C4 (Group 4)	Internal clearance larger than C3
Tolerance class	PN	Normal (ISO 492:2023)
Number of rows	1	Single-row design

Main Dimensions & Performance Data

d	160 mm	Bore diameter
D	340 mm	Outside diameter
B	114 mm	Width
C _r	1.910.000 N	Basic dynamic load rating, radial
C _{0r}	1.800.000 N	Basic static load rating, radial
C _{ur}	280.000 N	Fatigue load limit, radial
n _G	3.450 1/min	Limiting speed
n _{gr}	1.350 1/min	Reference speed
≈m	52,8 kg	Masa

Mounting dimensions

D _{a max}	323 mm	Maximum diameter of housing shoulder
--------------------	--------	--------------------------------------



Dimensions

r _{min}	4 mm	Minimum chamfer dimension
r _{1 min}	4 mm	Minimum chamfer dimension
s	9,9 mm	Axial displacement
E	300 mm	Raceway diameter outer ring
F	204 mm	Raceway diameter inner ring
D _{1 min}	286 mm	Minimum rib diameter outer ring
d ₁	221,55 mm	Maximum rib diameter inner ring

Temperature range

T _{min}	-30 °C	Operating temperature min.
T _{max}	150 °C	Operating temperature max.

Właściwości

-  Obciążenie promieniowe
-  Obciążenie osiowe jednokierunkowe
-  Smarowanie smarem
-  Smarowanie olejem
-  Bez uszczelnienia
-  Łożysko gabarytowe