



FAG

NJ316-E-XL-M1

Cylindrical roller bearing

Cylindrical roller bearing NJ..-E-XL-M1, with cage, single row, semi-locating bearing, 2 ribs on outer ring, 1 rib on inner ring, type NJ

X-life

Informacje techniczne



Twoja aktualna wersja produktu

Design	E	Increased Capacity Design
Cage	M1	Two Piece Brass Cage Roller Guided
Radial internal clearance	CN (Group N)	Normal internal clearance
Tolerance class	PN	Normal (ISO 492:2023)
Number of rows	1	Single-row design

Main Dimensions & Performance Data

d	80 mm	Bore diameter
D	170 mm	Outside diameter
B	39 mm	Width
C _r	300.000 N	Basic dynamic load rating, radial
C _{0r}	275.000 N	Basic static load rating, radial
C _{ur}	50.000 N	Fatigue load limit, radial
n _G	7.200 1/min	Limiting speed
n _{gr}	4.100 1/min	Reference speed
≈m	4,46 kg	Masa



Mounting dimensions

d _a min	92 mm	Minimum diameter shaft shoulder
d _a max	99 mm	Maximum diameter of shaft shoulder
D _a max	158 mm	Maximum diameter of housing shoulder
d _c min	114 mm	Minimum shaft shoulder

Dimensions

r _{min}	2,1 mm	Minimum chamfer dimension
r ₁ min	2,1 mm	Minimum chamfer dimension
s	0,7 mm	Axial displacement
E	151 mm	Raceway diameter outer ring
F	101 mm	Raceway diameter inner ring
D ₁ min	143,94 mm	Minimum rib diameter outer ring
d ₁	110,4 mm	Maximum rib diameter inner ring

Temperature range

T _{min}	-30 °C	Operating temperature min.
T _{max}	150 °C	Operating temperature max.

Additional information

HJ316-E	L-washer
---------	----------

Właściwości

	Obciążenie promieniowe
	Obciążenie osiowe jednokierunkowe
	Smarowanie smarem
	Smarowanie olejem
	Bez uszczelnienia