


**NK17/20-XL**

Needle roller bearing

Needle roller bearings NK, light series

X-life

Informacje techniczne



Twoja aktualna wersja produktu

Lubricant	Without	
Cage	Standard	
Cage feature	Standard	
Tolerance class	PN	Normal (DIN 620-2)

Main Dimensions & Performance Data

F_w	17 mm	Under roller diameter
D	25 mm	Outside diameter
C	20 mm	Width, outer ring
C_r	17.100 N	Basic dynamic load rating, radial
C_{0r}	20.400 N	Basic static load rating, radial
C_{ur}	3.600 N	Fatigue load limit, radial
n_G	22.600 1/min	Limiting speed
n_{gr}	15.000 1/min	Reference speed
$\approx m$	30 g	Masa

Dimensions

r_{min}	0,3 mm	Minimum chamfer dimension
-----------	--------	---------------------------



Temperature range

$T_{\min}$	-30 °C	Operating temperature min.
$T_{\max}$	120 °C	Operating temperature max.

Additional information

G17X25X3	Sealing ring
SD17X25X3	Sealing ring 2

Właściwości

	Obciążenie promieniowe
	Smarowanie smarem
	Smarowanie olejem
	Bez uszczelnienia
	Mala przestrzeń zabudowy