

**NKX70-XL**

Needle roller/axial ball bearing

Needle roller/axial ball bearings NKX, axial component, single direction, to DIN 5429, without end cap, for oil lubrication

X-life

Informacje techniczne



Twoja aktualna wersja produktu

Sealing	Without
Cage	Standard

Main Dimensions & Performance Data

F_w	70 mm	Bore diameter
D	85 mm	Outside diameter
C	40 mm	Height
C_r	50.000 N	Basic dynamic load rating, radial
C_{0r}	92.000 N	Basic static load rating, radial
C_a	43.000 N	Basic dynamic load rating, axial
C_{0a}	127.000 N	Basic static load rating, axial
C_{ur}	16.000 N	Fatigue load limit, radial
C_{ua}	6.300 N	Fatigue load limit, axial
n_G	2.400 1/min	Limiting speed
$\approx m$	554,34 g	Masa

Mounting dimensions

d_a	90,5 mm	Mounting dimension shaft shoulder
$r_{a \max}$	1 mm	Maximum recess radius



Dimensions

D 1 max	95,2 mm	Maximum outside diameter flange
D 2 max	95,2 mm	Maximum outside diameter flange
C 1	18 mm	Width of the axial bearing component
C 1	11 mm	Distance to lubrication hole
C 2	11 mm	Distance to lubrication hole
d w	70 mm	Bore diameter of shaft washer
r min	1 mm	Minimum chamfer dimension

Temperature range

T min	-30 °C	Operating temperature min.
T max	120 °C	Operating temperature max.

Additional information

IR60X70X25-XL

Suitable inner rings IR

Właściwości



Obciążenie promieniowe



Obciążenie osiowe jednokierunkowe



Smarowanie smarem



Smarowanie olejem



Bez uszczelnienia