




FAG

NN3034-AS-K-M-SP

Cylindrical roller bearing

Super precision cylindrical roller bearings
NN30...-AS-K-M-SP, non-locating bearing,
double row, with tapered bore, taper 1:12,
separable, with cage

Informacje techniczne



Twoja aktualna wersja produktu

Cage	M	Brass Cage
Tolerance class	SP	Tolerance class SP
Bore type	K	Tapered, taper 1:12
Change mark	A	Internal Variant A
Radial internal clearance	C1 (Group 1)	Internal clearance smaller than C2
Number of rows	2	Double-row design

Main Dimensions & Performance Data

d	170 mm	Bore diameter
D	260 mm	Outside diameter
B	67 mm	Width
C _r	450.000 N	Basic dynamic load rating, radial
C _{0r}	800.000 N	Basic static load rating, radial
C _{ur}	97.000 N	Fatigue load limit, radial
n _{G Grease}	3.100 1/min	Limiting speed for grease lubrication
n _{G Oil}	3.650 1/min	Limiting speed for oil lubrication
≈m	12,306 kg	Masa



Mounting dimensions

d _a	196 mm	Diameter shaft shoulder
h12		Diameter shaft shoulder tolerance
D _a	241 mm	Diameter of housing shoulder
H12		Shoulder diameter outer ring clearance
r _{a1} max	2,1 mm	Maximum recess radius

Dimensions

r ₁ min	2,1 mm	Minimum chamfer dimension
E	236 mm	Raceway diameter outer ring
n _s	9,5 mm	Width of lubricating groove
d _s	4,8 mm	Diameter lubrication hole
s	4,6 mm	Axial displacement

Temperature range

T _{min}	-30 °C	Operating temperature min.
T _{max}	150 °C	Operating temperature max.

Właściwości

-  Obciążenie promieniowe
-  Smarowanie smarem
-  Smarowanie olejem
-  Bez uszczelnienia