


NNTR60X150X75-2ZL

Yoke type track roller

Yoke type track roller NNTR..-2ZL, CRB, full complement roller set, two-row, with inner ring, 3 ribs on outer ring, not pallet changer

Informacje techniczne



Twoja aktualna wersja produktu

Sealing	2ZL	Sealing shields on both sides
---------	-----	-------------------------------

Main Dimensions & Performance Data

d	60 mm	Bore diameter
D	150 mm	Outside diameter
B	75 mm	Width, inner ring
C _{r w}	250.000 N	Basic dynamic load rating, radial
C _{0r w}	370.000 N	Basic static load rating, radial
C _{ur w}	57.000 N	Fatigue load limit, radial
n _{D G}	800 1/min	Speed on permanent grease lubrication
F _{0r per}	370.000 N	Permissible static load, radial
F _{r per}	330.000 N	Permissible dynamic load outer ring, radial
≈m	7,704 kg	Masa

Mounting dimensions

d ₂	78 mm	Stop diameter of thrust washer
D ₁	97 mm	Mounting dimension
d ₃	4 mm	Diameter lubrication hole
R	10.000 mm	Radius of outer ring outside profile
	3	Number of lubrication holes



Dimensions

C	73 mm	Width, outer ring
r _{min}	3 mm	Minimum chamfer dimension
r _{1 min}	2 mm	Minimum chamfer dimension

Właściwości

-  Obciążenie promieniowe
-  Obciążenie osiowe jednokierunkowe
-  Obciążenie osiowe dwukierunkowe
-  Smarowanie dożywotnie, bezobsługowe
-  Smarowanie smarem
-  Uszczelnienie dwustronne