




NSHS-606

Hydraulic cylinder, 700 bar

BETEX NSHS Hollow-piston cylinder, single-acting, spring return, 60T class

Informacje techniczne



Twoja aktualna wersja produktu

Series	NSHS	Hollow piston cylinder
Version	60T	Capacity class 60



Technical data

	60	Capacity class (tons)
s _p	152 mm	Stroke
A _p	89,6 cm²	Effective piston area
F _a	627 kN	Advance force, max.
P _{max}	700 bar	Operating pressure, max.
V _{oil}	1.360 cm³	Oil capacity
A	323,5 mm	Height, retracted
B	475,5 mm	Height, extended
D	158,6 mm	Outer diameter
E	125 mm	Cylinder bore diameter
F	90 mm	Plunger diameter
H	32 mm	Base to advance port
J	89 mm	Saddle diameter
K	12,5 mm	Saddle protrusion from plunger
O	2¾"-16 UN	Plunger female thread (UN)
P	25 mm	Plunger thread length
U	130 mm	Base mounting holes, bolt circle
V	1/2"-13 UN	Base mounting holes, thread (UNC)
Z	14 mm	Base mounting holes, thread depth
W	6½"-12 UN	Collar thread (UN)
X	50 mm	Collar thread, length
Y	54 mm	Center hole diameter
≈m	34 kg	Masa

Additional information

Hard chrome plated and hardened piston, Rolled inside of cylinder, Sandblasted outside with black nitride coating, Coupling with dust cap	Product specifics
--	-------------------