




NSSS-1510 [🔗](#)

Hydraulic cylinder, 700 bar

BETEX NSSS Standard cylinder, single-acting, spring return, 15T class

Informacje techniczne



Twoja aktualna wersja produktu

Series	NSSS	Standard cylinder
Version	15T	Capacity class 15

Technical data

	15	Capacity class (tons)
s _p	254,5 mm	Stroke
F _a	166 kN	Advance force, max.
P _{max}	700 bar	Operating pressure, max.
V _{oil}	604 cm³	Oil capacity
A	373 mm	Height, retracted
B	627,5 mm	Height, extended
D	73 mm	Outer diameter
E	55 mm	Cylinder bore diameter
F	40 mm	Plunger diameter
H	25 mm	Base to advance port
J	38 mm	Saddle diameter
K	9,6 mm	Saddle protrusion from plunger
O	1"-8 UN	Plunger female thread (UN)
P	25,4 mm	Plunger thread length
U	47,7 mm	Base mounting holes, bolt circle
V	3/8"-16 UNC	Base mounting holes, thread (UNC)
Z	13 mm	Base mounting holes, thread depth
W	2 3/4"-16 UN	Collar thread (UN)
X	30 mm	Collar thread, length
≈m	9,5 kg	Masa



Additional information

Hard chrome plated and hardened piston, Rolled inside of cylinder, Sandblasted outside with black nitride coating, Coupling with dust cap	Product specifics
---	-------------------