



NSSS-53

Hydraulic cylinder, 700 bar

BETEX NSSS Standard cylinder, single-acting, spring return, 5T class

Informacje techniczne



Twoja aktualna wersja produktu

Series	NSSL	Standard cylinder
Version	5T	Capacity class 5

Technical data

	5	Capacity class (tons)
s _p	76 mm	Stroke
F _a	49,5 kN	Advance force, max.
P _{max}	700 bar	Operating pressure, max.
V _{oil}	54 cm ³	Oil capacity
A	165 mm	Height, retracted
B	241 mm	Height, extended
D	38 mm	Outer diameter
E	30 mm	Cylinder bore diameter
F	25,4 mm	Plunger diameter
H	19 mm	Base to advance port
J	25 mm	Saddle diameter
K	6 mm	Saddle protrusion from plunger
O	3/4"-16 UN	Plunger female thread (UN)
P	14 mm	Plunger thread length
U	25 mm	Base mounting holes, bolt circle
V	1/4"-20 UNC	Base mounting holes, thread (UNC)
Z	14 mm	Base mounting holes, thread depth
W	1½"-16 UN	Collar thread (UN)
X	28 mm	Collar thread, length
≈m	1,5 kg	Masa



Additional information

Hard chrome plated and hardened piston, Rolled inside of cylinder, Sandblasted outside with black nitride coating, Coupling with dust cap	Product specifics
---	-------------------