FAG

# NU326-E-XL-M1

Cylindrical roller bearing

Cylindrical roller bearing NU..-E-XL-M1, with cage, single row, non-locating bearing, 2 ribs on outer ring, 0 ribs on inner ring (smooth), type NU, Running accuracy in P6

X-life

## Informacje techniczne




### Twoja aktualna wersja produktu

| | | |
|---|---|---|
| Design | E | Increased Capacity Design |
| Cage | M1 | Two Piece Brass Cage Roller Guided |
| Radial internal clearance | CN (Group N) | Normal internal clearance |
| Tolerance class | PN | Normal (ISO 492:2023) |
| Number of rows | 1 | Single-row design |







### Main Dimensions & Performance Data

| | | |
|---|---|---|
| d | 130 mm | Bore diameter |
| D | 280 mm | Outside diameter |
| B | 58 mm | Width |
| $C_r$ | 720.000 N | Basic dynamic load rating, radial |
| $C_{0r}$ | 720.000 N | Basic static load rating, radial |
| $C_{ur}$ | 87.000 N | Fatigue load limit, radial |
| $n_G$ | 4.250 1/min | Limiting speed |
| $n_{\vartheta r}$ | 2.340 1/min | Reference speed |
| ≈m | 17,92 kg | Masa |

Karta katalogowa jest jedynie przeglądem wymiarów i podstawowych nośności wybranego produktu. Zawsze należy stosować się do wszystkich dalszych informacji i instrukcji dotyczących tego produktu. Na naszej stronie internetowej znajduje się formularz kontaktowy umożliwiający wysłanie zapytania o dalsze informacje

## Mounting dimensions

| | | |
|---|---|---|
| $d_{a\ min}$ | 147 mm | Minimum diameter shaft shoulder |
| $d_{a\ max}$ | 164 mm | Maximum diameter of shaft shoulder |
| $d_{b\ min}$ | 169 mm | Minimum shaft shoulder |
| $D_{a\ max}$ | 263 mm | Maximum diameter of housing shoulder |
| $r_{a\ max}$ | 3 mm | Maximum recess radius |
| $r_{a1\ max}$ | 3 mm | Maximum recess radius |

## Dimensions

| | | |
|---|---|---|
| $r_{min}$ | 4 mm | Minimum chamfer dimension |
| $r_{1\ min}$ | 4 mm | Minimum chamfer dimension |
| s | 3,5 mm | Axial displacement |
| E | 247 mm | Raceway diameter outer ring |
| F | 167 mm | Raceway diameter inner ring |
| $D_{1\ min}$ | 235,2 mm | Minimum rib diameter outer ring |

## Temperature range

| | | |
|---|---|---|
| $T_{min}$ | -30 °C | Operating temperature min. |
| $T_{max}$ | 150 °C | Operating temperature max. |

## Właściwości

- $F_r$ Obciążenie promieniowe
- Smarowanie smarem
- Smarowanie olejem
- Bez uszczelnienia

Karta katalogowa jest jedynie przeglądem wymiarów i podstawowych nośności wybranego produktu. Zawsze należy stosować się do wszystkich dalszych informacji i instrukcji dotyczących tego produktu. Na naszej stronie internetowej znajduje się formularz kontaktowy umożliwiający wysłanie zapytania o dalsze informacje