



FAG


NUP212-E-XL-TVP2

Cylindrical roller bearing

Cylindrical roller bearing NUP..-E-XL-TVP2, with cage, single row, locating bearing, 2 ribs on outer ring, 1 rib on inner ring, rib washer internal, type NUP

X-life

Informacje techniczne





Twoja aktualna wersja produktu

Design	E	Increased Capacity Design
Cage	TVP2	Solid Window Cage made from PA66
Radial internal clearance	CN (Group N)	Normal internal clearance
Tolerance class	PN	Normal (ISO 492:2023)
Number of rows	1	Single-row design

Main Dimensions & Performance Data

d	60 mm	Bore diameter
D	110 mm	Outside diameter
B	22 mm	Width
C _r	112.000 N	Basic dynamic load rating, radial
C _{0r}	103.000 N	Basic static load rating, radial
C _{ur}	17.900 N	Fatigue load limit, radial
n _G	8.900 1/min	Limiting speed
n _{gr}	5.300 1/min	Reference speed
≈m	0,85 kg	Masa





Mounting dimensions

d 1	77,6 mm	Maximum rib diameter inner ring
D 1 min	96,1 mm	Minimum rib diameter outer ring
d a min	69 mm	Minimum diameter shaft shoulder
d c min	80 mm	Minimum shaft shoulder
D a max	101 mm	Maximum diameter of housing shoulder
r a max	1,5 mm	Maximum recess radius

Dimensions

r min	1,5 mm	Minimum chamfer dimension
r 1 min	1,5 mm	Minimum chamfer dimension
E	100 mm	Raceway diameter outer ring
F	72 mm	Raceway diameter inner ring
B 3	4 mm	Width of loose rib

Temperature range

T min	-30 °C	Operating temperature min.
T max	120 °C	Operating temperature max.

Właściwości

	Obciążenie promieniowe
	Obciążenie osiowe jednokierunkowe
	Obciążenie osiowe dwukierunkowe
	Smarowanie smarem
	Smarowanie olejem
	Bez uszczelnienia