



FAG


NUP2328-E-XL-M1

Cylindrical roller bearing

Cylindrical roller bearing NUP...-E-XL-M1, with cage, single row, locating bearing, 2 ribs on outer ring, 1 rib on inner ring, rib washer internal, type NUP

X-life

Informacje techniczne



Twoja aktualna wersja produktu

Design	E	Increased Capacity Design
Cage	M1	Two Piece Brass Cage Roller Guided
Radial internal clearance	CN (Group N)	Normal internal clearance
Tolerance class	PN	Normal (ISO 492:2023)
Number of rows	1	Single-row design

Main Dimensions & Performance Data

d	140 mm	Bore diameter
D	300 mm	Outside diameter
B	102 mm	Width
C _r	1.210.000 N	Basic dynamic load rating, radial
C _{0r}	1.390.000 N	Basic static load rating, radial
C _{ur}	221.000 N	Fatigue load limit, radial
n _G	3.950 1/min	Limiting speed
n _{gr}	1.620 1/min	Reference speed

≈m	37,2 kg	Masa
----	---------	------



Mounting dimensions

d ₁	195,4 mm	Maximum rib diameter inner ring
D _{1 min}	251,7 mm	Minimum rib diameter outer ring
d _{a min}	157 mm	Minimum diameter shaft shoulder
d _{c min}	198 mm	Minimum shaft shoulder
D _{a max}	283 mm	Maximum diameter of housing shoulder
r _{a max}	3 mm	Maximum recess radius

Dimensions

r _{min}	4 mm	Minimum chamfer dimension
r _{1 min}	4 mm	Minimum chamfer dimension
E	264 mm	Raceway diameter outer ring
F	180 mm	Raceway diameter inner ring
B ₃	16 mm	Width of loose rib

Temperature range

T _{min}	-30 °C	Operating temperature min.
T _{max}	150 °C	Operating temperature max.

Właściwości

	Obciążenie promieniowe
	Obciążenie osiowe jednokierunkowe
	Obciążenie osiowe dwukierunkowe
	Smarowanie smarem
	Smarowanie olejem
	Bez uszczelnienia