



FAG

NUP314-E-XL-TVP2-C3

Cylindrical roller bearing

Cylindrical roller bearing NUP...-E-XL-TVP2, with cage, single row, locating bearing, 2 ribs on outer ring, 1 rib on inner ring, rib washer internal, type NUP

X-life

Informacje techniczne



Twoja aktualna wersja produktu

Design	E	Increased Capacity Design
Cage	TVP2	Solid Window Cage made from PA66
Radial internal clearance	C3 (Group 3)	Internal clearance larger than CN
Tolerance class	PN	Normal (ISO 492:2023)
Number of rows	1	Single-row design

Main Dimensions & Performance Data

d	70 mm	Bore diameter
D	150 mm	Outside diameter
B	35 mm	Width
C _r	242.000 N	Basic dynamic load rating, radial
C _{0r}	222.000 N	Basic static load rating, radial
C _{ur}	40.500 N	Fatigue load limit, radial
n _G	6.300 1/min	Limiting speed
n _{gr}	4.500 1/min	Reference speed
≈m	2,85 kg	Masa



Mounting dimensions

d_1	97,4 mm	Maximum rib diameter inner ring
$D_1 \text{ min}$	126,8 mm	Minimum rib diameter outer ring
$d_a \text{ min}$	82 mm	Minimum diameter shaft shoulder
$d_c \text{ min}$	100 mm	Minimum shaft shoulder
$D_a \text{ max}$	138 mm	Maximum diameter of housing shoulder
$r_a \text{ max}$	2,1 mm	Maximum recess radius

Dimensions

r_{min}	2,1 mm	Minimum chamfer dimension
$r_1 \text{ min}$	2,1 mm	Minimum chamfer dimension
E	133 mm	Raceway diameter outer ring
F	89 mm	Raceway diameter inner ring
B_3	5,5 mm	Width of loose rib

Temperature range

T_{min}	-30 °C	Operating temperature min.
T_{max}	120 °C	Operating temperature max.

Właściwości

	Obciążenie promieniowe
	Obciążenie osiowe jednokierunkowe
	Obciążenie osiowe dwukierunkowe
	Smarowanie smarem
	Smarowanie olejem
	Bez uszczelnienia