




OCE20-DC-B-VA-FD

Radial insert ball bearing

Informacje techniczne



Main Dimensions & Performance Data

d	20 mm	Bore diameter
D _{SP}	47 mm	Outside diameter
C _{0r}	5.400 N	Basic static load rating, radial
C _{ur}	500 N	Fatigue load limit, radial
B ₁	33,3 mm	Locking collar total width
C _r	11.100 N	Basic dynamic load rating, radial
≈m	0,21 kg	Masa

Dimensions

C	16 mm	Width, outer ring
C ₂	20 mm	Sealing total width
S	12,7 mm	Distance raceway
d ₁	29,06 mm	Rib diameter inner ring
d ₃	37 mm	Outside diameter locking collar/locknut
W	3 mm	Width of flats

Temperature range

T _{min}	-35 °C	Operating temperature min.
T _{max}	120 °C	Operating temperature max.



Calculation factors

f_0	13,2	Calculation factor
-------	------	--------------------

Właściwości

	Obciążenie promieniowe
	Obciążenie osiowe jednokierunkowe
	Obciążenie osiowe dwukierunkowe
	Smarowanie dożywotnie, bezobsługowe
	Smarowanie smarem
	Uszczelnienie dwustronne
	Ochrona przed korozją
	Nieosiowość statyczna