





PCFTR17-XL

Flanged housing unit

Housing units PCFTR, three-bolt flanged housing units, cast iron, eccentric locking collar, P seals

X-life

Informacje techniczne



Twoja aktualna wersja produktu

Material	GG	Grey cast iron
----------	----	----------------

Main Dimensions & Performance Data

d	17 mm	Bore diameter
H ₂	81 mm	Height flange
U	32,1 mm	Total height unit
C _r	10.100 N	Basic dynamic load rating, radial
C _{0r}	4.750 N	Basic static load rating, radial
≈m	0,43 kg	Masa

Mounting dimensions

J	76,1 mm	Pitch circle diameter (holes)
N	11,5 mm	Fixing bore
n	3	Number of screwing holes



Dimensions

A	20 mm	Height housing
A ₁	11 mm	Thickness of flange
A ₂	10 mm	Distance raceway
H ₁	31 mm	Distance shaft axis
Q	M6	Connection thread for lubrication
d ₃	28,4 mm	Outside diameter eccentric locking collar

Additional information

1	Number of housings
CFTR03	Housing
GRAE17-XL-NPP-B	Bearing designation

Temperature range

T _{min}	-20 °C	Operating temperature min.
T _{max}	120 °C	Operating temperature max.