



IMAGE
COMING SOON





PCJT20-TV-FA125.5

Flanged housing unit

Flanged housing unit PCJT...-TV

Informacje techniczne



Twoja aktualna wersja produktu

Material	TV	Plastic
Manufacturing instruction	FA125.5	Bearing with Corrotect coating

Main Dimensions & Performance Data

d	20 mm	Bore diameter
L	63,8 mm	Flange width
H	114 mm	Height flange
U	38,9 mm	Total height unit
C _r	12.400 N	Basic dynamic load rating, radial
C _{0r}	6.000 N	Basic static load rating, radial
≈m	0,27 kg	Masa

Mounting dimensions

J	90 mm	Distance fixing bore
N	11 mm	Fixing bore
n	2	Number of screwing holes



Dimensions

A	26,5 mm	Height housing
A ₁	11,4 mm	Thickness of flange
A ₂	15,4 mm	Distance raceway
V	63,8 mm	Shoulder diameter housing
Q	1/4"-28 UNF	Connection thread for lubrication
d ₃	33 mm	Outside diameter locking collar

Additional information

1	Number of housings
CJT04-TV	Housing
GRAE20-NPP-B-FA107/125.5	Bearing designation
KASK04	Protecting cap

Temperature range

T _{min}	-35 °C	Operating temperature min.
T _{max}	100 °C	Operating temperature max.