




PCJT25-TV-FA125.5

Flanged housing unit

Flanged housing unit PCJT...-TV

Informacje techniczne



Twoja aktualna wersja produktu

Material	TV	Plastic
Manufacturing instruction	FA125.5	Bearing with Corrotect coating

Main Dimensions & Performance Data

d	25 mm	Bore diameter
L	70 mm	Flange width
H	130 mm	Height flange
U	40,5 mm	Total height unit
C _r	13.700 N	Basic dynamic load rating, radial
C _{0r}	7.100 N	Basic static load rating, radial
≈m	0,33 kg	Masa

Mounting dimensions

J	99 mm	Distance fixing bore
N	11 mm	Fixing bore
n	2	Number of screwing holes



Dimensions

A	29,1 mm	Height housing
A ₁	13,5 mm	Thickness of flange
A ₂	17 mm	Distance raceway
V	70 mm	Shoulder diameter housing
Q	1/4"-28 UNF	Connection thread for lubrication
d ₃	37,5 mm	Outside diameter locking collar

Additional information

1	Number of housings
CJT05-TV	Housing
GRAE25-NPP-B-FA107/125.5	Bearing designation
KASK05	Protecting cap

Temperature range

T _{min}	-35 °C	Operating temperature min.
T _{max}	100 °C	Operating temperature max.