





**PCJT55-XL**

Flanged housing unit

Housing units PCJT, two-bolt flanged housing units, cast iron, eccentric locking collar, P seals

X-life

Informacje techniczne



Twoja aktualna wersja produktu

|          |    |                |
|----------|----|----------------|
| Material | GG | Grey cast iron |
|----------|----|----------------|

Main Dimensions & Performance Data

|                 |          |                                   |
|-----------------|----------|-----------------------------------|
| d               | 55 mm    | Bore diameter                     |
| L               | 134 mm   | Flange width                      |
| H               | 222 mm   | Height flange                     |
| U               | 67,4 mm  | Total height unit                 |
| C <sub>r</sub>  | 43.500 N | Basic dynamic load rating, radial |
| C <sub>0r</sub> | 29.000 N | Basic static load rating, radial  |
| C <sub>ur</sub> | 1.340 N  | Fatigue load limit, radial        |
| ≈m              | 2,83 kg  | Masa                              |

Mounting dimensions

|   |        |                          |
|---|--------|--------------------------|
| J | 184 mm | Distance fixing bore     |
| N | 18 mm  | Fixing bore              |
| n | 2      | Number of screwing holes |



Dimensions

|                |         |                                   |
|----------------|---------|-----------------------------------|
| A              | 43,5 mm | Height housing                    |
| A <sub>1</sub> | 15 mm   | Thickness of flange               |
| A <sub>2</sub> | 31 mm   | Distance raceway                  |
| V              | 134 mm  | Shoulder diameter housing         |
| Q              | M6      | Connection thread for lubrication |
| d <sub>3</sub> | 76 mm   | Outside diameter locking collar   |

Additional information

|                 |                     |
|-----------------|---------------------|
| 1               | Number of housings  |
| CJT11           | Housing             |
| GRAE55-XL-NPP-B | Bearing designation |

Temperature range

|                  |        |                            |
|------------------|--------|----------------------------|
| T <sub>min</sub> | -20 °C | Operating temperature min. |
| T <sub>max</sub> | 120 °C | Operating temperature max. |