



**PSHE25-XL-N**

Plummer block housing unit

Plummer block housing units PSHE, cast iron housing, radial insert ball bearing with eccentric locking collar, P seals

X-life

Informacje techniczne



Twoja aktualna wersja produktu

|          |    |                                                   |
|----------|----|---------------------------------------------------|
| Groove   | N  | Cast iron housing with undercut slot for end caps |
| Material | GG | Grey cast iron                                    |

Main Dimensions & Performance Data

|     |         |               |
|-----|---------|---------------|
| d   | 25 mm   | Bore diameter |
| L   | 70 mm   | Length total  |
| H 2 | 70 mm   | Height        |
| ≈m  | 0,55 kg | Masa          |

Mounting dimensions

|   |         |                      |
|---|---------|----------------------|
| J | 50,8 mm | Distance fixing bore |
| K | M10     | Thread fixing bore   |

Dimensions

|     |         |                                       |
|-----|---------|---------------------------------------|
| H   | 36,5 mm | Distance shaft axis                   |
| A   | 36 mm   | Width (base)                          |
| A 1 | 21 mm   | Width (head)                          |
| Q   | M6      | Connection thread for lubrication     |
| S 1 | 23,5 mm | Distance of raceway to locking collar |



Additional information

|                 |                     |
|-----------------|---------------------|
| SHE05           | Housing             |
| GRAE25-XL-NPP-B | Bearing designation |
| KASK05          | Protecting cap      |

Temperature range

|                  |        |                            |
|------------------|--------|----------------------------|
| T <sub>min</sub> | -20 °C | Operating temperature min. |
| T <sub>max</sub> | 120 °C | Operating temperature max. |