


X-life

PWKRE52-2RS-XL

Stud type track roller

Stud type track rollers PWKRE...-2RS-XL, double row cylindrical roller bearings with particularly thick-walled outer ring, with a central rib, full complement cylindrical roller set and with a solid roller stud with fixing thread and a mounting aid, the outer ring is guided axially by the central rib and rolling elements, protected lip seal on both sides, with eccentric collar, X-life design

Informacje techniczne



Twoja aktualna wersja produktu

Sealing	2RS	Protected lip seal on both sides
Outer ring profile	IOP	Optimized INA-profile
Grease nipples	2x	Drive-fit lubrication nipple unmounted 2x
Relubrication feature	KS	Via head and stud
Assembling aid head	I6	Hexagon socket
Assembling aid stud	I6	Hexagon socket

Main Dimensions & Performance Data

D	52 mm	Outside diameter
d ₁	20 mm	Fit diameter of roller stud / stud
B	66 mm	Width
C _{rw}	25.500 N	Basic dynamic load rating, radial
C _{0rw}	33.500 N	Basic static load rating, radial
C _{urw}	4.200 N	Fatigue load limit, radial
n _{DG}	3.800 1/min	Speed on permanent grease lubrication
F _{0r per}	33.500 N	Permissible static load, radial
F _{r per}	21.800 N	Permissible dynamic load outer ring, radial
≈m	0,461 kg	Masa



Dimensions

B 1	25,6 mm	Width of thrust washer
B 2	40,5 mm	Bolt/stud length effectively
C	24 mm	Width, outer ring
C 1	0,8 mm	Protrusion outer ring to thrust washer
r min	1 mm	Minimum chamfer dimension
d 2	31 mm	Stop diameter of thrust washer
G	M20X1,5	Thread
l G	21 mm	Thread length
W	10 mm	Width of flats
d e	24 mm	Diameter of eccentric
B e	18 mm	Width, eccentric
e	1 mm	Eccentricity

Additional information

	NIPA2X7,5	Drive-fit lubrication nipple
M A	120 Nm	Tightening torque nut

Właściwości

-  Obciążenie promieniowe
-  Obciążenie osiowe jednokierunkowe
-  Obciążenie osiowe dwukierunkowe
-  Smarowanie dożywotnie, bezobsługowe
-  Smarowanie smarem
-  Uszczelnienie dwustronne