



FAG

QJ308-XL-MPA-S1-C3

Four-point contact bearing

Four point contact bearing QJ3...-XL-MPA, X-life, solid brass cage

X-life

Informacje techniczne



Twoja aktualna wersja produktu

Tolerance class	PN	Normal (ISO 492:2023)
Cage	MPA	Solid brass cage, outer ring guided
Dimensional / heat stabilization	S1	Rings dimensional stabilized up to 200°
Axial internal clearance	C3	Group 3 (C3), bigger than CN

Main Dimensions & Performance Data

d	40 mm	Bore diameter
D	90 mm	Outside diameter
B	23 mm	Width
C _r	84.000 N	Basic dynamic load rating, radial
C _{0r}	62.000 N	Basic static load rating, radial
C _{ur}	4.350 N	Fatigue load limit, radial
n _G	15.400 1/min	Limiting speed
n _{gr}	6.400 1/min	Reference speed
m	0,755 kg	Masa

Mounting dimensions

d _{a min}	49 mm	Minimum diameter shaft shoulder
D _{a max}	81 mm	Maximum diameter of housing shoulder
r _{a max}	1,5 mm	Maximum fillet radius



Dimensions

r _{min}	1,5 mm	Minimum chamfer dimension
D ₁	73,35 mm	Shoulder diameter outer ring
d ₁	56,65 mm	Shoulder diameter inner ring
a	45,5 mm	Distance between the apexes of the pressure cones
α	35 °	Contact angle

Temperature range

T _{min}	-30 °C	Operating temperature min.
T _{max}	200 °C	Operating temperature max.

Właściwości

-  Obciążenie promieniowe
-  Obciążenie osiowe jednokierunkowe
-  Obciążenie osiowe dwukierunkowe
-  Smarowanie smarem
-  Smarowanie olejem
-  Bez uszczelnienia