



RASEOC30-VA-FD

Plummer block housing unit

Informacje techniczne

Twoja aktualna wersja produktu

Material	VA	Stainless Steel
----------	----	-----------------

Main Dimensions & Performance Data

d	30 mm	Bore diameter
---	-------	---------------

L	165 mm	Length total
---	--------	--------------

H 2	80,9 mm	Height
-----	---------	--------

U	41,8 mm	Total width unit
---	---------	------------------

C r	16.700 N	Basic dynamic load rating, radial
-----	----------	-----------------------------------

C 0r	9.110 N	Basic static load rating, radial
------	---------	----------------------------------

C ur	760 N	Fatigue load limit, radial
------	-------	----------------------------

≈m	1,3 kg	Masa
----	--------	------

Mounting dimensions

J	121 mm	Distance fixing bore
---	--------	----------------------

N	17 mm	Width (slot)
---	-------	--------------

N 1	21 mm	Length (slot)
-----	-------	---------------

Dimensions

H	42,9 mm	Distance shaft axis
---	---------	---------------------

A	36 mm	Width (base)
---	-------	--------------

H 1	13 mm	Height (base)
-----	-------	---------------

S 1	23,8 mm	Distance of raceway to locking collar
-----	---------	---------------------------------------



Additional information

GEH.ASE06-VA-NAT	Housing
OCE30-DC-B-VA-FD	Bearing designation
KASK06-VA-G-NAT	Protecting cap

Temperature range

T _{min}	-20 °C	Operating temperature min.
T _{max}	100 °C	Operating temperature max.