




RCJ40-TV-VA-FD

Flanged housing unit

Flanged housing units, FD design

Informacje techniczne



Twoja aktualna wersja produktu

Special material	TV	Plastic housing
Material	TV-FD	Plastic for food industry
Corrosion resistant bearing	VA	Corrosion-resistant VA design

Main Dimensions & Performance Data

d	40 mm	Bore diameter
L	130 mm	Flange width
U	57,7 mm	Total height unit
C _r	28.500 N	Basic dynamic load rating, radial
C _{0r}	17.200 N	Basic static load rating, radial
C _{ur}	800 N	Fatigue load limit, radial
C _{0r G}	19.200 N	Load carrying capacity (housing)
≈m	0,99 kg	Masa

Mounting dimensions

J	102 mm	Distance fixing bore
N	14 mm	Fixing bore
W	4 mm	Width across flats



Dimensions

A	37,5 mm	Height housing
A ₁	17 mm	Thickness of flange
A ₂	23 mm	Distance raceway
B ₁	43,7 mm	Locking collar total width
B ₃	48 mm	Distance housing centre to cap end
S ₁	34,7 mm	Distance of raceway to locking collar
V	99 mm	Shoulder diameter housing
Q	1/4"-28 UNF	Connection thread for lubrication
d ₃	60,3 mm	Outside diameter locking device

Additional information

GEH.CJ08-TV-WHT	Housing
GE40-KRR-B-FA107-VA-FD	Bearing designation
KASK08-S-G-WHT	Protecting cap

Temperature range

T _{min}	-30 °C	Operating temperature min.
T _{max}	100 °C	Operating temperature max.